

Amendments to the Claims: This listing of claims will replace all prior versions, and listings, of claims in the application

Listing of Claims

1. (Currently Amended) [[-]] An articulated arm for an awning comprising:

an arm-(1) and a forearm-(2), with respective first and second ends-(1a, 1b; 2a, 2b), where the first end-(1a) of arm-(1) includes a securing configuration-(3) for ~~an~~ a first articulated joint to a fixed support, the second end-(1b) of the arm-(1) and the first end-(2a) or the forearm-(2) include respective articulation configurations-(4, 5) for a mutual articulated joint, and the second end-(2b) of the forearm-(2) is fitted with a support configuration-(6) for ~~an~~ a second articulated joint with a load bar, with a flexible pulling element-(7) being housed inside the arm-(1), with a first end-(7a) linked to an elastic element-(25) secured to a fixed point-(1c) on the arm-(1) and a second end-(7b) secured to the cited articulation configuration-(5) on the first end-(2a) on the forearm-(2), ~~characterised in that~~ wherein said articulation configuration-(5) of the first end-(2a) of the forearm-(2) comprises a core-(8) with an exterior surface shaped around a shaft-(9) that is transversal to ~~the~~ a longitudinal direction of said forearm and said articulation configuration-(4) of the second end-(1b) of the arm-(1) comprises a surrounding wall-(10) placed around said core-(8) and bearing means-(11a, 11b; 12a, 12b) being incorporated between said core-(8) and said surrounding wall-(10), which are coaxial with said shaft-(9) to guide rotation between both and provide support for the forearm-(2) on the arm-(1).

2. (Currently Amended) [[-]] An arm, in accordance with claim 1, ~~characterised in that~~ wherein between the interior surface of the surrounding wall-(10) and the core-(8), there is a ring-shaped space-(13) and the articulation configuration-(4) of the second end-(1b) of the arm-(1) includes an opening-(20) between said ring-shaped space-(13) and a hollow interior of the arm-(1) for the passage of said flexible pulling element-(7).

3. (Currently Amended) [[-]] An arm, in accordance with claim 2, ~~characterised in that~~ wherein said flexible pulling element-(7) is a belt that terminates at the second end-(7b) in a thickened configuration, which is secured to a corresponding housing-(5a) incorporated on said exterior surface of the core-(8).

4. (Currently Amended) [[-]] An arm, in accordance with claim 3, characterised ~~in that~~wherein said bearings means ~~(11a, 11b; 12a, 12b)~~ include at least one pair of first conical surfaces ~~(11a, 11b)~~ located close to, or on, the ends of the core ~~(8)~~ and at least one pair of second conical surfaces ~~(12a, 12b)~~ combined with the first conical surface and designed to slide over them, located at or close to the openings to an interior cavity defined by the surrounding wall ~~(10)~~.

5. (Currently Amended) [[-]] An arm, in accordance with claim 4, characterised ~~in that~~wherein at least one of said first or second conical surfaces ~~(11a, 11b; 12a, 12b)~~ of each pair is either made of or coated with a material with a low coefficient of friction in order to facilitate a sliding movement of the same in contact with the other of the first or second conical surfaces ~~(11a, 11b; 12a, 12b)~~ of each pair of surfaces in contact.

6. (Currently Amended) [[-]] An arm, in accordance with claim 5, characterised ~~in that~~wherein those first and/or second conical surfaces ~~(12a, 12b)~~ of each pair of surfaces in contact, which are made from a material having a low coefficient of friction, are incorporated into respective ring-shaped parts housed inside the core ~~(8)~~ or on the surrounding wall ~~(10)~~.

7. (Currently Amended) [[-]] An arm, in accordance with claim 6, characterised ~~in that~~wherein said ring-shaped parts are made from synthetic plastic.

8. (Currently Amended) [[-]] An arm, in accordance with claim 5, characterised ~~in that~~wherein at least one of the first and/or second conical surfaces ~~(11a, 11b; 12a, 12b)~~ is located respectively on the surrounding wall ~~(10)~~ and/or the core ~~(8)~~, or on auxiliary parts joined to them, and at least one of the first and/or second conical surfaces ~~(11a, 11b)~~ of each pair of surfaces in contact has either received an antifriction treatment or is coated with a material having a low coefficient of friction.

9. (Currently Amended) [[-]] An arm, in accordance with claim 4, characterised ~~in that~~wherein the articulation configuration ~~(5)~~ of the first end ~~(2a)~~ of the forearm ~~(2)~~ ~~consists of~~comprises a fork defined by first and second lateral supports parts ~~(17, 18)~~ that face each other, between which the core ~~(8)~~ is housed and secured by means of a securing pin ~~(19)~~ inserted axially through at least one hole ~~(17a, 18a)~~ in at least one of said first and second lateral supports ~~(17, 18)~~, said surrounding wall ~~(10)~~ remaining around the core ~~(8)~~ trapped between the two first conical surfaces ~~(11a, 11b)~~ and with second conical surfaces ~~(12a, 12b)~~ in contact with them.

10. (Currently Amended) [[-]] An arm, in accordance with claim 9, ~~characterised in that~~wherein the first lateral support-(17) includes a first hole-(17a) and one end of said core-(8), close to said first lateral support-(17) incorporates one of the first conical surfaces-(11a), and the second lateral support-(18) includes a second hole-(18a) with a slightly conical interior surface on which is seated a surface combined with an end part-(21), which incorporates the other of the first conical surfaces-(11b), with said end part-(21) including a central hole-(21a) aligned with the central hole-(8a) in the core-(8), which is aligned with said first hole-(17a) of the first lateral support-(17), and a pin-(19) is inserted and retained in a housing defined by said central hole-(21a), central hole-(8a) and the first hole-(17a).

11. (Currently Amended) [[-]] An arm, in accordance with claim 10, ~~characterised in that it includes some~~further comprising means for retaining said pin-(19) inside said housing against any movement in an axial direction.

12. (Currently Amended) [[-]] An arm, in accordance with claim 11, ~~characterised in that~~wherein the first hole-(17a) in the first lateral support-(17) and the central hole-(21a) of the end part-(21) have slightly conical surfaces and said pin-(19) is tubular with end portions that are widened against said slightly conical interior surfaces of the first hole-(17a) and the central hole-(21a) respectively.

13. (Currently Amended) [[-]] An arm, in accordance with claim 11-~~or~~ 12, ~~characterised in that it includes some~~further comprising plugs-(22, 23) for the first and second holes-(17a, 18a) in the first and second lateral supports-(17, 18), with said plugs-(22, 23) having securing configurations-(24) that are pressure inserted into the hollow pin-(19).

14. (Currently Amended) [[-]] An arm, in accordance with claim 4, ~~characterised in that~~wherein the articulation configuration-(5) of the first end-(2a) of the forearm-(2) comprises a lateral support-(14) that projects from the core-(8), and an end part-(15) joined to the free end of the core-(8) by means of at least one securing element-(16), where one of said first conical surfaces-(11a, 11b) are at the base of the core-(8) and another of said first conical surfaces-(11a, 11b) is incorporated into said end part-(15), leaving the surrounding wall-(10) trapped between the two first conical surfaces-(11a, 11b) and with the second conical surfaces-(12a, 12b) in contact with them.

15. (Currently Amended) [[-]] An arm, in accordance with claim 1, characterised ~~in that it comprises~~ further comprising at least one pair of stops ~~(26, 27)~~ located on an interior surface of the surrounding wall ~~(10)~~ or on said exterior surface of the core ~~(8)~~, in positions adapted to interfere during rotation of the forearm ~~(2)~~ with respect to the arm ~~(1)~~, with a protuberance ~~(28)~~ on the exterior surface of the core ~~(8)~~ or said interior surface of the surrounding wall ~~(10)~~ in order to limit the angle of rotation of the forearm ~~(2)~~ with respect to the arm ~~(1)~~.

16. (New) An arm, in accordance with claim 12, further comprising plugs for the first and second holes in the first and second lateral supports, with said plugs having securing configurations that are pressure inserted into the hollow pin.